
Kinderkraft




MINK PRO i-Size

USER GUIDE

MODEL: MINK PRO i-Size ECE R129.03 v.4.0

NOTE! Product graphics serve an illustrative function.






1.0 Usage

The car seat has been designed, tested and approved for use in accordance with the requirements of UN/ECE Regulation No. 129 concerning the approval of child improved restraint systems (UN/ECE R129/03).

• The MINK PRO car seat is designed for children from 40 cm to 75 cm tall. Maximum weight of the child: 13 kg.
• The car seat must be installed rearward facing (RWF) in the vehicle on the ISOFIX MINK FX base or with the use of the three-point car seat belt.
• The car seat can be installed in the car in the places indicated by the manufacturer in the vehicle manual. It is required to read the vehicle manufacturer's operating instructions. The child in the car seat is secured with internal safety harness.

NOTE! Never use the car seat in a forward facing position. NOTE! If the child exceeds the maximum length of the body, stop using the car seat.

Hight of the child	Car seat setting	Car seat mounting
40-75 cm		On a MINK FX base: ISOFIX connectors + support leg
		Three-point car seat belt



2.0 Safety instructions

Please take a few minutes to read this instruction manual in order to ensure the proper safety of your child.

• The car seat MUST NOT be installed on the vehicle seats mounted backwards or sideways.

• The car seat MUST NOT be placed on the vehicle seats with an active front air-bag.
• At the middle vehicle seat, the car seat can be installed only if there is a three-point car seat belt available.

• It is recommended to install the car seat only on the vehicle back seats.

!WARNINGS!

Please refer to your vehicle operating manual for information on the suitability of the vehicle seat for use with a car seat.

! Remember - the internal safety harness holding the child should be adjusted to the child's body shape and not twisted. For this reason, the child should not wear thick clothes under the safety harness.

! The car seat waist belts must run as low as possible across your child's pelvis to ensure optimum effect in the event of an accident.

! The car seat should be replaced when it has been subjected to violent stresses during a traffic accident.

! The car seat cannot be modified in any way without the acceptance of the relevant approval authority. Failure to install the car seat in accordance with the manufacturer's instructions may pose a threat to life and health of people.

! Protect the car seat from direct sunlight, otherwise your child may be burnt by its heated parts. Protect your child and the car seat from sunlight.

! NEVER leave your child unattended in the car seat.

! Make sure that the luggage and other objects are adequately secured, in particular on the rear parcel shelf, as they can cause injuries in the event of a collision.

! The car seat CANNOT be used without a cover.

! DO NOT use replacement covers, other than those recommended by the manufacturer, as the cover is an integral part of the safety system of the car seat.

! DO NOT use any other attachment points than those described in the instruction manual and marked on the car seat.

! All hard elements and plastic parts of the car seat must be placed and installed in a way preventing them from being trapped by the sliding seat or vehicle doors under normal vehicle operating conditions.

! Regularly check the technical condition of the car seat, pay special attention to the fixing points, seams and adjusting parts. It is important to ensure that all mechanical elements are fully operational. Never grease or oil parts of the car seat.

! DO NOT use the car seat if its parts are damaged or loose.


! In the event of an emergency, it is important to quickly unfasten the car seat belts. This means that the release button of the safety harness is not fully secured; make sure your child does not play with the safety harness.

! Set a good example for your child and always fasten your car seat belt. An adult who is not fastened with a car seat belt can also pose a threat to a child.

! Make sure that the car seat is correctly secured before each journey in the car.

! The car seat must be secured at all times, even when not in use. The car seat that is not fastened can injure the passengers even during emergency braking.

! On some vehicle seats made of delicate materials, the use of car seats may leave marks and/or discolouration. In order to prevent it, you can place a blanket, towel or similar product under the car seat.




A: Headrest part of the insert
B: Fasteners
C: Seat belt
D: Insert


3.0 Securing the child


3.1 Using the insert


1. Connect the headrest part of the insert with the rest of it using snap fasteners
2. Unfasten the safety harness
3. Move the safety harness to the sides of the car seat.
4. Put the insert in place


The baby insert is used to protect the newborns. The baby insert is suitable for children less than 60 cm tall.












A: Safety harness adjustment button
B: Internal safety harness
C: Headrest adjustment handle

3.2 Headrest height adjustment together with internal safety harness

1. Unfasten the safety harness
2. Loosen the inner safety harness as much as possible by pressing the safety harness adjustment button while pulling on it. **Remember! Do not pull on the shoulder pads.**
3. Place the safety harness on the sides of the car seat
4. Place your child in the car seat
5. Adjust the headrest by pulling the adjustment handle and set it to the height appropriate for your child. When the headrest is locked in place, you will hear a characteristic clicking sound.


The inner safety harness changes its height when you adjust the headrest height.



Adjust the appropriate height of the inner safety harness so that the harness enters the seat backrest at the height of the child's shoulders or slightly above

3.3 Setting the position of the handle





To set the car seat handle in the selected position, perform the following steps.





1. Press the car seat handle adjustment button on both sides at the same time to unlock the handle
2. Release the buttons and move the handle to one of the four available positions.
3. When the handle is locked in a selected position, you will hear a characteristic "click".

A: Handle adjustment button

3.3.1 Positions of the handle

Position for installation with the use of car seat belt	Position for carrying and mounting on the stroller frame and ISOFIX base
	
Position for placing the child in the car seat	Position for car seat storage
	







4.0 Using the sun shade


The sun shade is used to prevent direct sunlight on the child's face

Installation of the sun shade:
1. Set the car seat handle to the carrying position
2. Place the fastener of the sun shade in the appropriate place on the handle of the car seat

To remove the sun shade, follow the above steps in reverse order.








A: Handle adjustment button
B: Waist belt guide


5.0 Installation in the vehicle


5.1 Installation of the car seat rearward facing using seat belt

NOTE! Before starting the installation, make sure that the seat is equipped with a three-point car seat belt and that the air-bag is disabled.

1. To make it easier to install the car seat in the vehicle, set the car seat handle in the carrying position. **Remember to remove the car seat sun shade before adjusting the handle**
2. Place the car seat on the seat and press it against the backrest of the car seat
3. Extend the car seat belt as far as possible. Pull the car seat belt through both waist safety harness guides (marked green) in the car seat. Fasten the car seat belt buckle - you will hear a characteristic "click".








C: Rear belt guide of the car seat

4. Set the car seat handle in an installation position with the use of a car seat belt - facing the vehicle seat. The handle should rest on the vehicle seat.
5. Insert the shoulder part of the car seat belt into the rear car seat belt guide marked green. **The car seat belt should be tightened and passed through all points of the car seat marked green**
6. Tighten the belt to make sure it holds the car seat tightly on the vehicle seat




A: Base support leg
B: ISOFIX connectors release button
C: ISOFIX base connector
D: Correct installation indicator of the ISOFIX connectors
E: Vehicle seat ISOFIX connectors
F: Correct installation indicator of the support leg


5.2 Installing the car seat rearward facing using the ISOFIX- MINK FX base

Remember to deactivate the air-bag before installing the car seat on the vehicle seat!

5.2.1 Base installation:

1. Before placing the base on the vehicle seat, unfold the base support leg.
2. Place the base on the vehicle seat and, while pressing the ISOFIX connector release buttons, pull it out of the base as much as possible. Do this on both sides.
3. Hook the ISOFIX base connectors onto the car connectors. You will hear a click and the correct installation indicator will turn green
4. Move the base as close to the backrest of the vehicle seat as possible. When moving the base, push it evenly against the vehicle seat until the base rests evenly on the backrest of the vehicle seat.
5. Press the support leg height adjustment button. Extend the support leg until it rests on the floor of the vehicle.
6. Check if the support leg indicator changed its colour to green






NOTE! Never install the support leg on the storage box in the floor of the car - the storage box can break during an accident; if in doubt, refer to the vehicle manual.

NOTE! The support leg must never be unsupported, and no objects can be placed under it.

IMPORTANT! Make sure that the support leg serves as a support and does not raise the bottom of the car seat above the plane of the vehicle seat.


Note! The base must be placed close to the backrest of the vehicle seat!




A: Handle adjustment button
B: Car seat installation indicator on the ISOFIX base

5.2.2 Installation of the car seat on the ISOFIX MINK FX base:

1. Set the handle in the mounting position on the ISOFIX base.
2. Position the car seat so that it is rearward-facing and insert it into the base - you should hear a characteristic click and the car seat should be locked in the base.
3. Check whether the car seat is properly installed on the base by verifying whether the installation indicator turns green.






A: Base lock lever
B: Car seat release button

5.3 Removing the car seat from the ISOFIX base and removing the base

5.3.1 Removing the car seat:


1. Slide the base lock lever and hold it, then press the car seat release button.
2. Lift the car seat up.





A: Support leg extension adjustment button
B: Support leg extension
C: ISOFIX release button
D: Base ISOFIX connector

5.3.2 Removing the base:

1. Slide the support leg up using the leg extension adjustment button
2. Press the ISOFIX release buttons and slide the arm into the base. Do this on both sides.
3. Remove the base from the vehicle seat and remove it from the vehicle.
4. Fold the support leg by inserting it under the base in the designated place.







A: Handle adjustment button
B: Stroller adapters

6.0 Handling of the car seat on the stroller frame


NOTE! Before inserting or removing the car seat from the frame of the stroller, always use the parking brake on the frame to prevent the stroller from rolling away uncontrollably.


Installation:

1. Set the car seat handle in the position for installation on the stroller frame.
2. Guide the stroller frame adapters into the slots in the car seat and push them down
until you hear a "click" sound


NOTE! Please refer to the stroller manual for information on car seat compatibility.

The MINK PRO i-Size seat is compatible with Kinderkraft strollers and strollers from other manufacturers with universal adapters. In order to verify whether the stroller is equipped with universal adapters, contact its manufacturer.






A: Button for removing the car seat from the stroller adapters (buttons are located under the cover)



Removing the stroller:

1. Press the buttons on both sides to remove the car seat from the stroller adapters.
2. Remove the car seat from the adapters.


The location of the buttons for removing the car seat from the adapters is marked with arrows





7.0 Maintenance instructions


7.1 Removing the cover

1. Remove the sun shade from the car seat handle
2. Loosen the inner safety harness as much as possible, then slide the shoulder pads off the safety harness.
3. Remove the cover from the headrest of the car seat
4. Remove the fabric from the inside of the car seat backrest










5. Unhook the elastic ribbon from the car seat shell.
6. Pull out the two ribbons (the cover and the sun shade ribbons) from the slot.
7. To remove the cover from the back of the car seat, slightly stretch the plastic element and slide the fabric of the cover and the sun shade out of the lock. Remove the cover from the rest of the car seat by inserting the internal elements through its holes.
8. Remove the cover from the edge of the car seat by pulling it slightly against the waist safety harness guides



9. Remove the cover from the car seat starting from its front part.

7.2 Installing the cover

To put the cover back on - just reverse the above sequence of actions. Start by installing the cover on the shell of the car seat and finally on the headrest part. Align the cover with the attachment points on the car seat.

NOTE! Never use strong detergents or bleaches.

NOTE! The internal safety harness system must not be dismantled! Never disassemble individual parts of the internal safety harness.

The full text of the Warranty Terms and Conditions is available at WWW.KINDERKRAFT.COM

7.3 Cleaning

Only the original cover should be used, as it is an essential element of the safety of the car seat.

- The cover can be removed. Machine wash in warm water (up to 30°C) using a mild detergent. Leave to dry. Do not spin, do not tumble dry, do not use bleach.
- The pads can be removed and hand washed (below 30°C) in warm soapy water. Leave to dry, do not spin, do not tumble dry.
- The insert should not be washed; if necessary, it can be cleaned by hand because it is not possible to dry the foam inside.

The plastic parts can be cleaned with water and a mild detergent. Do not use strong detergents (e.g. solvents). Do not use oil.

The safety harness can be cleaned with a damp cloth and lukewarm water using a mild detergent. Avoid soaking the belts wet.

Kinderkraft

(AR) إضمان مصلحة عملائنا ـ نحن في خدمتكم! إذا كانت لديكم أي مشكلة مع المنتج الذي حصلتم عليه، فيجر ى الاتصال بنا بالطريقة التي تفضلونها!

(CS) V zájmu péče o naše klienty - jsme rádi k dispozici! Pokud jste se setkali s nějakým problémem v souvislosti s obdrženým výrobkem, kontaktujte nás způsobem, který vám nejvíce vyhovuje!

(DE) In Sorge für unsere Kunden - stehen wir gerne zu Ihrer Verfügung! Wenn Sie auf ein Problem mit dem erhaltenen Produkt treffen, treten Sie bitte mit uns in Kontakt in der bequemsten Weise für Sie!

(EN) In the interests of our Clients - we are at your disposal! If you have a problem with the product you received, contact us in the most convenient way for you!

(ES) ¡Por el bien de nuestros clientes, estamos a su disposición! ¡Si tiene cualquier problema con el producto recibido, póngase en contacto con nosotros de forma más cómoda para usted!

(FR) Dans l'intérêt de nos clients - nous sommes à votre disposition! Si vous avez un problème avec le produit que vous avez reçu, Contactez-nous de la manière la plus pratique pour vous!

(HU) Bármikor állunk az ügyfeleink rendelkezésére! Ha az átvett termékkel kapcsolatban valamilyen problémába ütkozott, az Onnek legmegfelelobb módon vegye fel velünk a kapcsolatot!

(IT) Prendersi cura dei nostri Clienti - siamo alla Vostra disposizione! Se hai incontrato un problema con il prodotto che hai ricevuto. Contattaci nel modo piu conveniente per te!

(NL) In het belang van onze klanten - staan wij ter beschikking! Als u een probleem met het ontvangen product tegenkomt, neemt contact met ons op via de manier die u het makkelijkste vindt!

(PL) W trosce o naszych Klientów - jesteśmy do dyspozycji! Jeśli napotkałeś problem dotyczacy otrzymanego produktu, skontaktuj sie z nami w najbardziej dogodny dla Ciebie sposób!

(PT) Para o conforto dos nossos Clientes - estamos sempre à sua disposição! Se tiver qualquer problema com o nosso produto, entre em contacto connosco de modo mais confortável para si!

(RO) In interesul clienţilor noştri - suntem la dispozitia dumneavoastră! Dacă aveţi o problema cu produsul pe care l-aţi primit, contactaţi-ne in modul cel mai convenabil pentru dvs.!

(RU) заботясь о наших клиентах, мы находимся в вашем распоряжении. Если вы столкнулись с проблемой, связанной с полученные продукто, свяжитесь с нами наиболее удобным для вас способ!

(SK) Náš zákazník je pre nás dôležitý - sme vám k dispozícii! Ak máte akýkoľvek problém súvisiaci s doručeným produktom, kontaktujte nás spôsobom, ktorý vám najviac vyhovuje!

(SV) I våra kunders intresse - vi står till ditt förfogande! Om du har problem med den produkt du fick, kontakta oss på det mest praktiska sättet för dig!

International contact:
support@kinderkraft.com
+44 20 4525 0748

kinderkraftofficial
kinderkraft
kinderkraftofficial

منتج/VÝROBCE/HERSTELLER/MANUFACTURER/FABRICANTE/FABRICANT/ GYARTÓ/FABBRICANTE/FABRIKANT/PRODUCENT/FABRICANTE/PRODUCĂTOR/ ПРОИЗВОДИТЕЛЬ/VÝROBCA/TILLVERKARE:

4Kraft Sp. z o.o. ul. Tatrzańska 1/5
60-413 Poznań, Poland